



## 3518 / 3518 P

**3518** - Compactor with vibratory smooth roller drum

**3518 P** - Compactor with vibratory padfoot drum



- ▶ Ergonomic driver seat for perfect all-round visibility
- ▶ Clear information display
- ▶ Excellent hill climbing ability via self-locking differential
- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Hydrostatic steering
- ▶ Optimum ease of maintenance, long service intervals



# 3518 / 3518 P

3518 - Compactor with vibratory smooth roller drum  
3518 P - Compactor with vibratory padfoot drum



	3518	3518 P
<b>Weights</b>		
Operating weight with ROPS	kg 17605	17805
Operating weight with cab	kg 17825	18025
Operating weight, max.	kg 21420	19760
Axle load, front/rear	kg 10785/7040	10985/7040
Load per tyre, rear	kg 3520	3520
Static linear load, front	kg/cm 48,6	
French classific., data/class	68,73/VM4	68,77/VPM4
<b>Machine dimensions</b>		
Max. working width	mm 2220	2220
Lateral overhang, left/right	mm 85/85	85/85
Ground clearance, left/right	mm 510/510	510/510
Ground clearance, centre	mm 425	425
Turning radius, inside	mm 4435	4180
Drum thickness, front	mm 45	35
Number of padfeet		150
Height of the padfeet	mm 100	100
Front area of padfeet	cm <sup>2</sup> 152	152
Size of tyres, rear	AW 23.1-26 12 PR	TR 23.1-26 12 PR
<b>Diesel engine</b>		
Manufacturer	DEUTZ	DEUTZ
Type	TCD 2012 L06 2V	TCD 2012 L06 2V
Number of cylinders	6	6
Power rat. ISO 14396, kW/PS/rpm	155,0/210,8/2300	155,0/210,8/2300
Power rating SAE J1349, kW/HP/rpm	155,0/207,7/2300	155,0/207,7/2300
Emissions standard EU/USA	III A / Tier 3	III A / Tier 3
Fuel tank, capacity	L 290	290
<b>Drive</b>		
Hydrostatic drive, front/rear	Hydraulic motor/axle	Hydraulic motor/axle
Speed, working gear	km/h 0-4,2/0-5,6/0-6,7	0-3,8/0-5,3/0-5,9
Speed, transportation gear	km/h 0-11,4	0-11,1
Climbing ability, vibration on/off	% 48/53	55/60

**Vibration system**  
Hydrostatic drive

<b>Vibration</b>		
Vibration frequency, front, I/II	Hz 27/30	27/30
Amplitude, front, I/II	mm 2,00/1,19	1,93/1,15
Centrifugal force, front, I/II	kN 331/243	331/243

<b>Steering</b>		
Steering, type	Articulated steering	Articulated steering
Steering, actuation	hydrostatic, steering wheel	hydrostatic, steering wheel
Steering angle +/-	° 32	32
Oscillation angle +/-	° 10	10

**Equipment**  
Spring-mounted driver seat, Double-sided access, Seat console, can be moved and swivelled laterally, Continuously variable hydrostatic all-wheel drive, Excellent engine power with traction control, Swivelling steering and instrument console, Modern information and indicator display, Tilttable GRP bonnet

**Optional equipment**  
Spotlights, Exterior and interior mirrors, Radio, Heating with dust-free ventilation, Air conditioning, ROPS/FOPS, Sound insulation, Sunroof, HCQ compression meter, HCQ printer, HCQ GPS compression documentation, Tachograph

<b>Total length</b>	L	6440	6210
<b>Width</b>	B	2390	2390
<b>Total height</b>	H	2980	3050
<b>Wheel base</b>	A	3252	3165
<b>Roller drum width</b>	X	2220	2220
<b>Drum diameter</b>	D	1600	1784
<b>Width over tyres</b>	Y	2160	2160
<b>Diameter of tyres</b>	R	1565	1565
<b>Height loading, min.</b>	HI	2325	2350

