



3412 VIO / 3412 HT VIO

3412 VIO - Compactor with VIO smooth roller drum

3412 HT VIO - Compactor with VIO smooth roller drum



- ▶ Ergonomic driver seat for perfect all-round visibility
- ▶ Clear information display
- ▶ Excellent hill climbing ability via self-locking differential
- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Hydrostatic steering
- ▶ Optimum ease of maintenance, long service intervals



3412 VIO / 3412 HT VIO

3412 VIO - Compactor with VIO smooth roller drum
3412 HT VIO - Compactor with VIO smooth roller drum



		3412 VIO	3412 HT VIO
Weights			
Operating weight with ROPS	kg	11705	11705
Operating weight with cab	kg	11925	11925
Operating weight, max.	kg	14990	14990
Axle load, front/rear	kg	6425/5500	6425/5500
Load per tyre, rear	kg	2750	2750
Static linear load, front	kg/cm	30,0	30,0
French classific., data/class		41,2/VM3	41,2/VM3
Machine dimensions			
Max. working width	mm	2140	2140
Lateral overhang, left/right	mm	55/55	55/55
Ground clearance, left/right	mm	465/465	465/465
Ground clearance, centre	mm	375	375
Turning radius, inside	mm	3780	3780
Drum thickness, front	mm	30	30
Size of tyres, rear		AW 23.1-26 12 PR	AW 23.1-26 12 PR
Diesel engine			
Manufacturer		DEUTZ	DEUTZ
Type		TCD 2012 L04 2V	TCD 2012 L04 2V
Number of cylinders		4	4
Power rat. ISO 14396, kW/PS/rpm		100,0/136,0/2300	100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm		100,0/134,0/2300	100,0/134,0/2300
Emissions standard EU/USA		III A / Tier 3	III A / Tier 3
Fuel tank, capacity	L	290	290
Drive			
Hydrostatic drive, front/rear		Hydraulic motor/axle	Hydraulic motor/axle
Regulation, infinitely variable			Hammtronic/manual
Speed, infinitely variable	km/h		0 - 14,0
Speed, working gear	km/h	0-3,7/0-5,4/0-6,0	
Speed, transportation gear	km/h	0-11,7	
Climbing ability, vibration on/off	%	54/59	59/64
Vibration system			
Hydrostatic drive			
Vibration			
Vibration frequency	Hz	33	33
Amplitude, vibration	mm	1,89	1,89
Centrifugal force, vibr.	kN	279	279
Oscillation			
Oscillation frequency	Hz	33	33
Tangential amplitude, oscillation	mm	1,74	1,74
Oscillation force	kN	279	279
Steering			
Steering, type		Articulated steering	Articulated steering
Steering, actuation		hydrostatic, steering wheel	hydrostatic, steering wheel
Steering angle +/-	°	35	35
Oscillation angle +/-	°	10	10
Equipment			
Spring-mounted driver seat, Double-sided access, Seat console, can be moved and swivelled laterally, Continuously variable hydrostatic all-wheel drive, Excellent engine power with traction control, Swivelling steering and instrument console, Modern information and indicator display, Tilttable GRP bonnet			
Optional equipment			
Spotlights, Exterior and interior mirrors, Radio, Heating with dust-free ventilation, Air conditioning, ROPS/FOPS, Sound insulation, Sunroof, HCQ compression meter, HCQ printer, HCQ GPS compression documentation, Tachograph			

Total length	L	5870	5870
Width	B	2250	2250
Total height	H	2990	2990
Wheel base	A	3060	3060
Roller drum width	X	2140	2140
Drum diameter	D	1504	1504
Width over tyres	Y	2130	2130
Diameter of tyres	R	1565	1565
Height loading, min.	HI	2325	2325

