Dynapac CC1000 Plus

Double drum vibratory rollers





Technical data

| Masses Masses | |
|-----------------------------|------------|
| Max. operating mass | 1,750 kg |
| Operating mass (incl. ROPS) | 1,685 kg |
| Module mass (front/rear) | 790/895 kg |

| Traction | |
|--------------------------|------|
| Speed range (Dual/TC/AS) | 0-9 |
| Vertical oscillation | ±13° |
| Theor. gradeability | 40 % |

| Compaction | |
|---------------------------------|---------------|
| Centrifugal force | 17 kN |
| Nominal amplitude | 0.4 mm |
| Static linear load (front/rear) | 7.9/8.9 kg/cm |
| Vibration frequency | 70 Hz |
| Water tank | 190 I |

| Engine | |
|------------------------|----------------------------|
| Manufacturer/Model | Kubota D1105-E4B T4f |
| Туре | Water cooled diesel |
| Rated power, SAE J1995 | 18 kW (24 hp) @ 2,800 rpm |
| Fuel tank capacity | 23 |


| Hydraulic system | |
|--------------------------------|--|
| Driving | Axial piston pump with variable displacement and servo. 2 radial piston motors with constant displacement. |
| Vibration | Gear pump/motors with constant displacement. |
| Steering | Gear pump with constant displacement. |
| Service brake | Hydrostatic in forward and reverse lever. |
| Parking/ Emergency brake | Failsafe brake in both drums. |


Dynapac CC1000 Plus

Double drum vibratory rollers



Technical data





| Dimensions | |
|-----------------------------|----------|
| A. Wheelbase | 1,350 mm |
| B. Width | 1,070 mm |
| C. Curb clerance | 465 mm |
| D. Drum diameter | 584 mm |
| H2. Height, w/o ROPS/cab | 1,585 mm |
| K. Ground clearance | 250 mm |
| L1. Length | 2,040 mm |
| L2. Length (ROPS) | 2,095 mm |
| O1. Overhang, right | 35 mm |
| O2. Overhang, left | 35 mm |
| R1. Turning radius, outside | 2,750 mm |
| S. Drum shell thickness | 13 mm |
| W. Drum width | 1,000 mm |
| α. Steering angle | ±34° |

| Equipment package | | |
|--------------------------------------|----------|----------|
| CC Plus Package | Included | Optional |
| Backup alarm | • | |
| CE sign | • | |
| Comfort seat | | |
| Cup/can holder | • | |
| Driving lights, right or left handed | | • |
| Dual forward/reverse control | | • |
| Foldable ROPS incl. seat belt | • | |
| Large Watertank, 190 I | • | |
| Rotating beacon | • | |
| Rotating beacon, ignition controlled | | • |
| Spring loaded scrapers | | • |
| Sprinkler timer | | |
| Vibr. shut off, front or rear drum | | |
| Working lights | • | |



Optional equipment

3" seatbelt, Biodegradable hydraulic fluid, Cert. fire protection (SBF 127), Decal risk location (GOST), Fire extinguisher, Hearing protectors, Licence plate light, Rear view mirror (traffic view), Service kit 50/500/1000 h, Side direction lights (driving lights required), Slow moving vehicle sign, Special color (one or two), Tool set, Water tank cover (lockable)