## Dynapac CC1200C Plus Combi rollers





## **Technical data**

4,	Masses			
	Max. operating mass		2,570 kg	
	Operating mass (incl. ROPS)		2,430 kg	
	Module mass (front/rear)		1,260/1,170 kg	
Ó	Traction			
	Speed range (Dual/TC/AS)		0-9,5 km/h	
	Theor. gradeability		63 %	
₩ V	Compaction			
	Wheel load		290 (kg/wheel)	
	Tyre type (smooth)		640x240-15 33 kN 0.5 mm	
	Centrifugal force			
	Nominal amplitude			
	Nominal amplitude		0.0 mm	
	Static linear load		10.5 kg/cm	
	Static linear load		10.5 kg/cm	

Engine			
Manufacturer/Mo	odel	Kubota D1703-M	
Туре		Water cooled	
Rated power, SA	E J1995	26 kW (35 hp ) @ 2,800 rpm	
Fuel tank capaci	ty	50 I	
Hydraulic syste	: system		
Driving	Axial piston pump with variable displacement. Radial piston motors (3) with constant displacement. Gear pump/motors with constant displacement. Gear pump with constant displacement.		
Vibration			
Steering			

Hydrostatic in forward and reverse lever.

Failsafe multidisc on drum and wheel motors.

Service brake

Parking/ Emergency brake

Find us locally at www.atlascopco.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.


rce\_cc1200c\_plus\_en-20140905.112525.pdf 2014-09-05 11:25


## Dynapac CC1200C Plus Combi rollers



Backup alarm, Working lights

## **Technical data**





$\mathbf{V}$	Equipment package					
CC Plus Package	Included	Optiona				
Backup alarm						
Brake release	•					
CE sign						
Driving lights, right or left handed		•				
Dual arm rest	•					
Dual forward/reverse control		•				
Dual frequency		•				
Flow divider	1	•				
Foldable ROPS incl. seatbelt	•					
Rotating beacon	•					
Rotating beacon, ignition controlled	1	•				
Slideable comfort seat	•					
Slideable lux seat		-				
Spring loaded scrapers		-				
Sprinkler timer	•					
Vibr. shut off, front drum	•	Î				
Working lights	1.					



Optional equipment

Standard equipment

3" seatbelt, Biodegradable hydraulic fluid, Cert. Fire protection (SBF 127), Decal risk location (GOST), Fire extinguisher, Foot rest Hearing protectors, Licence plate light, Rear view mirror (traffic view), Service kit 50/500/1000H, Side direction lights (driving lights required), Slow moving vehicle sign, Special color (one or two), Tool set, Towing eyelet, Water tank cover (lockable)

Find us locally at www.atlascopco.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.