Dynapac CC3300

Double drum vibratory rollers





Technical data

Masses	
Max. operating mass	9,900 kg
Operating mass (incl. ROPS)	9,000 kg
Module mass (front/rear)	4,500/4,500 kg

Traction	
Speed range (Dual/TC/AS)	0-12
Vertical oscillation	±7°
Theor. gradeability	35 %

Compaction	
Split drums	Yes
Centrifugal force (high/low amplitude)	79/64 kN
Nominal amplitude (high/low)	0.5/0.2 mm
Static linear load (front/rear)	26.0/26.0 kg/cm
Vibration frequency (high/low amplitude)	48/67 Hz
Water tank	750

Engine	
Manufacturer/Model	Deutz TCD 3.6 IIIB/T4i
Туре	Water cooled turbo Diesel
Rated power, SAE J1995	75 kW (100 hp) @ 2,200 rpm
Fuel tank capacity	130 l

Engine		
Manufacturer/Model	Cummins QSB 3.3 IIIA/T3	
Туре	Water cooled turbo Diesel	
Rated power, SAE J1995	74 kW (99 hp) @ 2,200 rpm	


Hydraulic system	n
Driving	Axial piston pump with variable displacement Axial piston motors (4) with variable displacement
Vibration	Axial piston pumps (2) with variable displacement Axial piston motors (2) with constant dispacement
Steering	Gear pump with constant displacement.
Service brake	Hydrostatic in forward and reverse lever.
Parking/ Emergency brake	Failsafe multidisc brake in both drums.


Dynapac CC3300

Double drum vibratory rollers



Technical data





Dimensions	
A. Wheelbase	3,340 mm
B. Width	1,940 mm
C. Curb clerance	715 mm
D. Drum diameter	1,150 mm
H1. Height, with ROPS/cab	2,990 mm
H2. Height, w/o ROPS/cab	2,270 mm
K. Ground clearance	270 mm
L. Length	4,490 mm
R. Turning radius, outside	5,305 mm
S. Drum shell thickness	17 mm
W. Drum width	1,730 mm
α. Steering angle	±32°