## Dynapac F1700C

## Tracked pavers





### **Technical data**

Masses	
Weight (incl. V340TV)	8.80 t

Dimensions	
Basic width	1.70 m
Working width, hydraulic extendable	3.40 m
Working width, maximum (incl. extension boxes)	4.40 m
Working width, minimum (with reducing shoe)	0.70 m

Capacity	
Placement thickness (max)	270 mm
Theoretical placement capacity	350 t/h

Material hopper	
Capacity	4.7 m <sup>3</sup> (10.1 t)
Dumping height	600 mm
Hopper width, internal	2,900 mm

Traction	
Paving speed	0-32 m/min
Transport speed	3.8 km/h

Engine	
Manufacturer/Model	Deutz TD 2011 L04
Rated power, SAE J1995	52 kW (71 hp ) @ 2,300 rpm
Electrical system	24V
Fuel tank capacity	98 I

Undercarriage	
Crawler length	2,060 mm
Crawler width	260 mm
Final drive	Direct drive over transmissions

Conveyor	
Conveyor type	Dual bar feeder
Conveyor width	2 x 350mm


<b>FF</b> Auger	
Auger diameter	350 mm
Auger control	Two reversible augers with Ultrasonic control

# Dynapac F1700C

## Tracked pavers



#### **Technical data**



Dimensions	
A. Axle track	2,060 mm
B1. Width, max.	3020 mm
B2. Width, standard	1,700 mm
B3. Width, center of tracks	1,300 mm
C1. Track width	260 mm
H1. Height, max.	3,150 mm
H2. Height, transport	2,950 mm
L1. Length	4,945 mm
L3. Length, hopper	1,800 mm



Suitable screeds	7				
Model	Basic width	Working width, hydraulic extendable	Working width, maximum	Compacting elements	Heating system
Dynapac V340V	1.70 m	3.40 m	4.40 m	Vertical stroke vibration	N/A
Dynapac V340VE	1.70 m	3.40 m	4.40 m	Vertical stroke vibration	Electrical
Dynapac V340TV	1.70 m	3.40 m	4.40 m	Vertical impact tamper/vibration	Propane (LPG)
Dynapac V340TVE	1.70 m	3.40 m	4.40 m	Vertical impact tamper/vibration	Electrical