Dynapac F1700W

Wheeled pavers





Technical data

Masses	
Weight	8.50

Dimensions	
Basic width	1.70 m
Working width, hydraulic extendable	3.40 m
Working width, maximum (incl. extension boxes)	4.10 m
Working width, minimum (with reducing shoe)	0.60 m

Capacity	
Placement thickness (max)	270 mm
Theoretical placement capacity	300 t/h

Material hopper	
Capacity	4.7 m³ (9.50 t)
Dumping height	600 mm
Hopper width, internal	3,040 mm

Traction	
Paving speed	0 -32 m/min
Transport speed	18.0 km/h

Engine			
Manufacturer/Model	Deutz TD 2011 L04		
Rated power	52 kW (71 hp) @ 2,300 rpm		
Electrical system	24V		
Fuel tank capacity	65 I		

Undercarriage	
Tyre size	385/65-R22,5
Front wheels	4 x 460/250
Final drive	2 speed hydrostatic drive
Wheel drive	2 rear wheels

Conveyor	
Conveyor type	Dual bar feeder
Conveyor width	2 x 350 mm


FFF Auger	
Auger diameter	350 mm
Auger control	Automatic with ultrasonic sensors

Dynapac F1700W

Wheeled pavers



Technical data



Dimensions	
A. Wheelbase	1,590 mm
B1. Width, max.	3,020 mm
B2. Width, standard	1,700 mm
H1. Height, max.	3,150 mm
H2. Height, transport	2,950 mm
H3. Height, driver's plattform	2,350 mm
L1. Length	4,950 mm
L3. Length, hopper	1,650 mm



Suitable screeds					
Model	Basic width	Working width, hydraulic extendable	Working width, max.	Compacting elements	Heating system
Dynapac V340V	1.70 m	3.40 m	4.40 m	Vertical stroke vibration	Propane (LPG)
Dynapac V340VE	1.70 m	3.40 m	4.40 m	Vertical stroke vibration	Electrical