



3412 / 3412 P

3412 - Compactor with vibratory smooth roller drum

3412 P - Compactor with vibratory padfoot drum



- ▶ Ergonomic driver seat for perfect all-round visibility
- ▶ Clear information display
- ▶ Excellent hill climbing ability via self-locking differential
- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Hydrostatic steering
- ▶ Optimum ease of maintenance, long service intervals



3412 / 3412 P

3412 - Compactor with vibratory smooth roller drum
3412 P - Compactor with vibratory padfoot drum



		3412	3412 P
Weights			
Operating weight with ROPS	kg	11980	12080
Operating weight with cab	kg	12200	12300
Operating weight, max.	kg	15270	13830
Axle load, front/rear	kg	6705/5495	6805/5495
Load per tyre, rear	kg	2747,5	2747,5
Static linear load, front	kg/cm	31,3	
French classific., data/class		42,2/VM3	43,4/VP3
Machine dimensions			
Max. working width	mm	2140	2140
Lateral overhang, left/right	mm	55/55	55/55
Ground clearance, left/right	mm	465/465	465/465
Ground clearance, centre	mm	375	375
Turning radius, inside	mm	3780	3690
Drum thickness, front	mm	30	20
Number of padfeet			140
Height of the padfeet	mm		100
Front area of padfeet	cm ²		152
Size of tyres, rear		AW 23.1-26 12 PR	TR 23.1-26 12 PR
Diesel engine			
Manufacturer		DEUTZ	DEUTZ
Type		TCD 2012 L04 2V	TCD 2012 L04 2V
Number of cylinders		4	4
Power rat. ISO 14396, kW/PS/rpm		100,0/136,0/2300	100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm		100,0/134,0/2300	100,0/134,0/2300
Emissions standard EU/USA		III A / Tier 3	III A / Tier 3
Fuel tank, capacity	L	290	290
Drive			
Hydrostatic drive, front/rear		Hydraulic motor/axle	Hydraulic motor/axle
Speed, working gear	km/h	0-3,7/0-5,4/0-6,0	0-3,8/0-5,2/0-6,4
Speed, transportation gear	km/h	0-11,7	0-11,3
Climbing ability, vibration on/off	%	51/56	57/62
Vibration system			
Hydrostatic drive			
Vibration			
Vibration frequency, front, I/II	Hz	30/40	30/40
Amplitude, front, I/II	mm	1,91/0,90	1,87/0,88
Centrifugal force, front, I/II	kN	256/215	256/215
Steering			
Steering, type		Articulated steering	Articulated steering
Steering, actuation		hydrostatic, steering wheel	hydrostatic, steering wheel
Steering angle +/-	°	35	35
Oscillation angle +/-	°	10	10
Equipment			
Spring-mounted driver seat, Double-sided access, Seat console, can be moved and swivelled laterally, Continuously variable hydrostatic all-wheel drive, Excellent engine power with traction control, Swivelling steering and instrument console, Modern information and indicator display, Tiltbale GRP bonnet			
Optional equipment			
Spotlights, Exterior and interior mirrors, Radio, Heating with dust-free ventilation, Air conditioning, ROPS/FOPS, Sound insulation, Sunroof, HCQ compression meter, HCQ printer, HCQ GPS compression documentation, Tachograph			

Total length	L	5870	5705
Width	B	2250	2250
Total height	H	2990	3010
Wheel base	A	3060	3015
Roller drum width	X	2140	2140
Drum diameter	D	1504	1684
Width over tyres	Y	2130	2130
Diameter of tyres	R	1565	1565
Height loading, min.	HI	2325	2325

