





HW 90B/10 / HW 90B/12

HW 90B/10 - Static three-wheel roller
HW 90B/12 - Static three-wheel roller



HAMM

- Two ergonomic driver seats
- Hydrostatic drive
- > 2 weight classes: 10-12 t, can be loaded to 12-14 t
- ► Ideal load distribution between front and rear drum
- Water pressure sprinkler, electronically controlled
- Large water tank with 400 I long application time
- 4-cylinder turbo-engine

HW 90B/10 - Static three-wheel roller HW 90B/12 - Static three-wheel roller



HW 90B/10 HW 90B/12 Weights 10690 Operating weight with ROPS kg 12480 Operating weight with cab kg 10670 12460 15000 Operating weight, max. kg 13210 4090/6580 5110/7350 Axle load, front/rear kg Static linear load, front/rear kg/cm 37,2/53,9 46,5/60,2 **Machine dimensions** 2020 2020 mm Max. working width Ground clearance, centre 385 385 mm 2365 Turning radius, inside 2365 mm Drum thickness, front 27 mm Drum thickness, rear 27 27 mm Diesel engine DEUTZ DEUTZ Manufacturer Туре TD 2011 L04 I TD 2011 L04 I Number of cylinders Power rat. ISO 14396, kW/PS/rpm Power rating SAE J1349, kW/HP/rpm 53,7/73,0/2500 53,7/72,0/2500 53,7/73,0/2500 53,7/72,0/2500 III A / Tier 4i III A / Tier 4i Emissions standard EU/USA Fuel tank, capacity 140 140 L Drive Hydrostatic drive, front/rear -/planetary gear 0 - 10,2 -/planetary gear 0 - 10,2 Speed, infinitely variable km/h Climbing ability, with/no ballast 25/40 25/40 Steering Pivot steering, front Pivot steering, front Steering, type Steering, actuation hydrostatic, steering wheel hydrostatic, steering wheel Steering angle +/-Oscillation angle +/-Sprinkler system Water sprinkler, type Pressure Pressure Actuation, sprinkling interval/manual interval/manual

Equipment

Spring-mounted driver seat, 2 comfort seats, Automatic starter interlock, Operating hours counter, Speedometer

Optional equipment

Water tank, capacity

ROPS comfort cab, 360°-glazing, Exterior and interior mirrors, Electric fan, Heating with dust-free ventilation, Rotating beacon, Seat belt, Sound insulation, Sunroof, Edge pressing and cutting equipment, Tilting axle, Hydraulic differential lock, Coir mats

400

400

-		4000	1000
Total length	L	4890	4890
Width	В	2020	2020
Total height	H	3220	3220
Wheel base	Α	2830	2830
Drum width, front	Χv	1100	1100
Drum diameter, front	Dv	1250	1250
Drum width, rear	Xh	610	610
Drum diameter, rear	Dh	1550	1550
Height loading, min.	HI	2400	2400

