



HD 14 TT

HD 14 TT - Rubber-wheeled roller



- ▶ Optimum front view due to concaving front end
- ▶ Ergonomic driver platform
- ▶ Modern instrument panel
- ▶ Low machine height
- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Crab steering
- ▶ Convenient maintenance and service



HD 14 TT

Weights

Operating weight with ROPS	kg	3470
Operating weight, max.	kg	4320
Axle load, front/rear	kg	1605/1865
Load per tyre, front/rear	kg	550/466,25

Machine dimensions

Max. working width	mm	1276
Lateral overhang, left/right	mm	-/-
Ground clearance, left/right	mm	-/-
Ground clearance, centre	mm	305
Turning radius, inside	mm	2602
Size of tyres, front/rear		10.5/80-16

Diesel engine

Manufacturer	KUBOTA
Type	V2203-M-E3B
Number of cylinders	4
Power rat. ISO 14396, kW/PS/rpm	34,6/47,1/2700
Power rating SAE J1349, kW/HP/rpm	34,6/46,4/2700
Emissions standard EU/USA	III A / Tier 4i
Fuel tank, capacity	L 73

Drive

Hydrostatic drive, front/rear		Hydr. motor/hydr. motor
Speed, infinitely variable	km/h	0-10,0
Climbing ability	%	40

Steering

Steering, type		Articulated steering
Steering, actuation		hydrostatic, steering wheel
Steering angle +/-	°	33
Oscillation angle +/-	°	8

Sprinkler system

Water sprinkler, type		Pressure
Actuation, sprinkling		interval/manual
Water tank, capacity	L	290

Equipment

Crab steering up to 50 mm, Spring-mounted driver seat, Comfort seat with seat belt, 2 multifunction drive levers, Operating hours counter, Indicator lights, Emergency stop switch

Optional equipment

Comfort driver cab, Lighting per German Road Traffic Regulations, 2 spotlights on ROPS, Rotating beacon, Special colour, Sunroof, Sound insulation, Back-up alarm

Total length	L	2856	
Width	B	1296	
Total height	H	2720	
Wheel base	A	1950	
Width over tyres	Y	1127/1276	
Diameter of tyres	R	810/810	
Height loading, min.	HI	1820	

